

Техникийн тодорхойлолт

Баримтын скайнер /FUJITSU Document Scanner ScanSnap iX500 эсхүл түүнтэй дүйцэх/

/5 ширхэг/

Д/д	Бараа болон холбогдох үйлчилгээний нэр		Техникийн тодорхойлолт болон стандарт
1.	Scanner Type		Automatic Document Feeder (ADF), Duplex Scanning
2.	Scanning Modes		Color, Grayscale, Monochrome, Automatic (color / grayscale / monochrome detection ⁽³⁾)
3.	Image Sensor		Color CIS (Contact Image Sensor) x 2 (front / back)
4.	Light Source		3 Color LED (Red / Green / Blue)
5.	Optical Resolution		600 x 600 dots per inch (dpi)
6.	Scanning Speed (A4 portrait) ⁽¹⁾	Auto Mode ⁽²⁾	Simplex or Duplex, 25 pages per minute (ppm)
		Normal Mode	Color & Grayscale 150 dpi, Monochrome 300 dpi, Simplex/Duplex, 25 ppm
		Better Mode	Color & Grayscale 200 dpi, Monochrome 400 dpi, Simplex/Duplex, 25 ppm
		Best Mode	Color & Grayscale 300 dpi, Monochrome 600 dpi, Simplex/Duplex, 25 ppm
		Excellent Mode ⁽³⁾	Color & Grayscale 600 dpi, Monochrome 1200 dpi, Simplex/Duplex, 7 ppm
7.	Document Size	Normal Mode without Carrier Sheet	A4, A5, A6, B5, B6, Business Card, Post Card, Letter, Legal and Custom Size. Max: 216 mm X 360 mm (8.5 in. X 14.17 in.), Min: 50.8 mm X 50.8 mm (2 in. X 2 in.). Automatically recognizes document size.
		Normal Mode with Carrier Sheet ⁽³⁾	Use of a Carrier Sheet permits the scanning of A3, B4, 279.4 mm X 431.8 mm (11 in. x 17 in.) and photographs as well as the document sizes listed above.
		Long Paper Scanning ⁽³⁾⁽⁴⁾	863mm (34 in.)
8.	Multi-feed Detection		Supported (Standard) ultrasonic multi-feed detection sensor
9.	Paper Weight (thickness)		40 g/m2 to 209 g/m2 (11 lb. to 56 lb.)
10.	Paper Chute Capacity ⁽⁵⁾		Maximum 50 sheets (A4, 80g/m2 or 21 lb.)
11.	Interface		USB 3.0 (USB 2.0 / 1.1 Compatible) ⁽⁶⁾
12.	Wi-Fi Interface ⁽⁷⁾	Observed Standards	IEEE802.11b / IEEE802.11g / IEEE802.11n
		Communication Mode	Infrastructure Mode
		Frequency ⁽⁸⁾	2.412 GHz to 2.462 GHz / 2.412 GHz to 2.472 GHz
		Communication Distance	Indoors, 50 m (Recommended: indoors, within 25 m) *May vary depending on surrounding environment and the access point to be connected

		Security ⁽⁹⁾	WPA-PSK (TKIP / AES), WPA2-PSK (TKIP / AES), WEP (64-bit / 128-bit)
		Easy Installation	WPS2.0 supported (button / PIN code)
13.	Power Requirement		AC Adapter AC 100 V to 240 V, 50 / 60 Hz
14.	Power Consumption / USB Connected	Operating Mode	20 W or less
15.		Sleep Mode	1.6 W or less
16.		Auto Standby (Off) Mode	less than 0.4 watt
17.			
18.	Power Consumption / Wi-Fi Connected	Operating Mode	20 W or less
19.		2.5 W or less	2.5 W or less
20.		Auto Standby (Off) Mode	less than 0.4 watt
21.	Operation Environment	Temperature	5 °C to 35 °C (41 °F to 95 °F)
22.		Relative Humidity	20 % to 80 % (non-condensing)
23.	Dimensions (W x D x H) ⁽¹⁰⁾		292 mm x 159 mm x 168 mm (11.5 in. x 6.2 in. x 6.6 in.)
24.	Device Weight		3.0 kg (6.62 lb.)